

2024

# Bitsman Auto

Egoldvan Industry Co., Limited

Sole overseas sales agent for Suzhou Kejun.

# CONTENTS

01

Company  
Profile

02

Factory  
Certifications

03

Product  
Category

04

Contact  
Us

01

# Company Profile

---



# Company Profile

Bitsman

--The top tire mobility kit provider



We have more than ten years of experience in auto parts design and development, and are led by a management team that has worked for top domestic auto manufacturers. As a Tier 1 supplier, we maintain close working relationships with thirteen automobile manufacturers. In addition, our tire repair tool factory is one of the few factories that can pass SAIC's winter experiment, which further reflects our professional technical strength and excellent product quality.

02

# Factory Certifications

---

# Factory Certifications



Quality Certificate: IATF16949

Test institute: TUV

ITAF NO.: No.0349777

Certificate No.: 44111182579



# Factory Certifications

Environmental System Certificate: ISO14001

Test Institute: Shanghai Ingeer

Certificate No.: 11721EU006808 ROS

# Bitsman

--The top tire mobility kit provider



# Factory Certifications



We have 25 patents, including 3 invention patents.



03

# Product Category

---

# Product Category



**Tire Sealant**



**Tire Mobility Kit**



**Inflator**





## Tire Mobility Kit300

The Bitsman Tire Mobility Kit 300 is a must-have for every car owner and is designed to help them easily and quickly repair holes in their tires while on the road without the need for a spare tire. The tool consists of a bottle of patching fluid and an inflation pump that effectively repairs holes in tires (holes  $\leq 6$ mm in diameter) while providing inflation so you can get right back on the road. With Bitsman's automatic tire repair tool, you can avoid the hassle of changing tires on the side of the road and get to your destination safely and quickly.







# Product Category



## Tire Mobility Kit300

Project		Specification value
Product name		Tire Mobility Kit
Model number		KIT300
Overall Dimensions		250mm*150mm*90mm
Gross weight		1.45kg
Tire sealant Volume		300mL
Expiration date of tire sealant		On-board condition 5 years
Tire sealant performance	Applicable Temp Range	-30°C~70°C
	Puncture Diameter	Fix the damaged nails which is ≤6mm
Tire sealant melting point		115°C no boiling
Tire sealant freezing point		-70°C no solidification
PH value		7~9
Smell		Slight mild rubber oder
Color		Milky white

Our warranty is valid for one year. The sealant must be regularly shaken within 6 months from the time of receiving the goods at the port. Failure to do so may result in the sealant's failure, which is not covered by our warranty.

Optional Product List		
Product Name	Product picture	Product Use Method
Battery Clamp		One end is a cigarette lighter female socket interface, and the other end is a positive and negative level red and black chuck, a red positive pole and a black negative pole correspond to the positive and negative poles of the vehicle-mounted battery, and the positive and negative levels of the vehicle-mounted battery are marked with a plus sign and a minus sign.
Extension Hose		Suitable for vehicles with large and long body size, such as the power cord and inflation hose length of the inflator can not reach part of the tire air nozzle after plugging in the cigarette lighter, the use of this extension hose can solve the problem, the longest extension length of the hose is 3 meters
Gas Needle		English French air valve adapter, basketball football pin connector
The Nail Puller		The nail puller consists of a nail head, a nail pulling plate, a nail groove and a handle. When in use, align the nail head with the nail, press the handle to make the nail head enter the nail hole, and then lift the handle to pull out the nail.





## Tire Mobility Kit450

The Bitsman Tire Mobility Kit 450 is a must-have for every car owner and is designed to help them easily and quickly repair holes in their tires while on the road without the need for a spare tire. The tool consists of a bottle of patching fluid and an inflation pump that effectively repairs holes in tires (holes  $\leq 6\text{mm}$  in diameter) while providing inflation so you can get right back on the road. With Bitsman's automatic tire repair tool, you can avoid the hassle of changing tires on the side of the road and get to your destination safely and quickly.



# Product Category







--The top tire mobility kit provider



## Tire Mobility Kit450

Project		Specification value
Product name		Tire Mobility Kit
Model number		KIT450
Overall Dimensions		250mm*150mm*90mm
Gross weight		1.5kg
Tire sealant Volume		450mL
Expiration date of tire sealant		On-board condition 5 years
Tire sealant performance	Applicable Temp Range	-30°C ~ 70°C
	Puncture Diameter	Fix the damaged nails which is ≤6mm
Tire sealant melting point		115°C no boiling
Tire sealant freezing point		-70°C no solidification
PH value		7~9
Smell		Slight mild rubber oder
Color		Milky white

Our warranty is valid for one year. The sealant must be regularly shaken within 6 months from the time of receiving the goods at the port. Failure to do so may result in the sealant's failure, which is not covered by our warranty.

Optional Product List		
Product Name	Product picture	Product Use Method
Battery Clamp		One end is a cigarette lighter female socket interface, and the other end is a positive and negative level red and black chuck, a red positive pole and a black negative pole correspond to the positive and negative poles of the vehicle-mounted battery, and the positive and negative levels of the vehicle-mounted battery are marked with a plus sign and a minus sign.
Extension Hose		Suitable for vehicles with large and long body size, such as the power cord and inflation hose length of the inflator can not reach part of the tire air nozzle after plugging in the cigarette lighter, the use of this extension hose can solve the problem, the longest extension length of the hose is 3 meters
Gas Needle		English French air valve adapter, basketball football pin connector
The Nail Puller		The nail puller consists of a nail head, a nail pulling plate, a nail groove and a handle. When in use, align the nail head with the nail, press the handle to make the nail head enter the nail hole, and then lift the handle to pull out the nail.





## Tire Sealant450

- The tire sealant is researched, produced and made by our factory independently. The main raw material of the tire sealant are natural latex , propylene glycol and so on, which don't corrode type and rim.
- The tire sealant can fix the worn tire quickly with the use of inflator.(we can fix the damaged punctures which is  $\leq 6\text{mm}$ )







# Product Category



## Tire Sealant450

Project		Specification value
Product name		Tire Sealant
Model number		SLT450
Overall Dimensions		Φ89×138.5
Gross weight		0.65kg
Tire sealantVolume		450mL
Expiration date of tire sealant		On-board condition 5 years
Tire sealant performance	Applicable Temp Range	-30℃ ~ 70℃
	Puncture Diameter	Fix the damaged nails which is ≤6mm
Tire sealantmelting point		115℃ no boiling
Tire sealantfreezing point		-70℃ no solidification
PH value		7~9
Smell		Slight mild rubber oder
Color		Milky white

Our warranty is valid for one year. The sealant must be regularly shaken within 6 months from the time of receiving the goods at the port. Failure to do so may result in the sealant's failure, which is not covered by our warranty.

Optional Product List		
Product Name	Product picture	Product Use Method
Battery Clamp		One end is a cigarette lighter female socket interface, and the other end is a positive and negative level red and black chuck, a red positive pole and a black negative pole correspond to the positive and negative poles of the vehicle-mounted battery, and the positive and negative levels of the vehicle-mounted battery are marked with a plus sign and a minus sign.
Extension Hose		Suitable for vehicles with large and long body size, such as the power cord and inflation hose length of the inflator can not reach part of the tire air nozzle after plugging in the cigarette lighter, the use of this extension hose can solve the problem, the longest extension length of the hose is 3 meters
Gas Needle		English French air valve adapter, basketball football pin connector
The Nail Puller		The nail puller consists of a nail head, a nail pulling plate, a nail groove and a handle. When in use, align the nail head with the nail, press the handle to make the nail head enter the nail hole, and then lift the handle to pull out the nail.





## Tire Sealant300

- The tire sealant is developed, produced and made by our factory independently. The main raw material of the tire sealant is natural latex, propylene glycol and so on, which don't corrode tire and rim.
- The tire sealant can fix the worn tire quickly with the use of inflator .(we can fix the damaged punctures which is  $\leq 6\text{mm}$ )



# Product Category

**Bitsman**




--The top tire mobility kit provider



## Tire Sealant300

Project		Specification value
Product name		Tire Sealant
Model number		SLT300
Overall Dimensions		Φ89×138.5
Gross weight		0.5kg
Tire sealant Volume		300mL
Expiration date of tire sealant		On-board condition 5 years
Tire sealant performance	Applicable Temp Range	-30℃ ~ 70℃
	Puncture Diameter	Fix the damaged nails which is ≤φ6mm
Tire sealant melting point		115℃ no boiling
Tire sealant freezing point		-70℃ no solidification
PH value		7~9
Smell		Slight mild rubber oder
Color		Milky white

Our warranty is valid for one year. The sealant must be regularly shaken within 6 months from the time of receiving the goods at the port. Failure to do so may result in the sealant's failure, which is not covered by our warranty.

Optional Product List		
Product Name	Product picture	Product Use Method
Battery Clamp	 A black battery clamp with a cigarette lighter female socket interface on one end and two red and black chucks on the other.	One end is a cigarette lighter female socket interface, and the other end is a positive and negative level red and black chuck, a red positive pole and a black negative pole correspond to the positive and negative poles of the vehicle-mounted battery, and the positive and negative levels of the vehicle-mounted battery are marked with a plus sign and a minus sign.
Extension Hose	 A yellow, coiled extension hose.	Suitable for vehicles with large and long body size, such as the power cord and inflation hose length of the inflator can not reach part of the tire air nozzle after plugging in the cigarette lighter, the use of this extension hose can solve the problem, the longest extension length of the hose is 3 meters
Gas Needle	 A small, black and silver gas needle.	English French air valve adapter, basketball football pin connector
The Nail Puller	 A red-handled nail puller with a black handle and a silver nail head.	The nail puller consists of a nail head, a nail pulling plate, a nail groove and a handle. When in use, align the nail head with the nail, press the handle to make the nail head enter the nail hole, and then lift the handle to pull out the nail.





## Inflator

The product is a device designed for quick and efficient use of inflating tire for vehicles. The inflator can be used for inflating, deflating, and tire pressure detection; The tire sealant can repair the broken tire with the use of the inflator (can repair the  $\leq \phi 6\text{mm}$  of the punctures breakage); At the same time, it can also inflate objects such as blue balls, footballs, and balloons.

This versatile tool is ideal for both home and professional use, providing a reliable and convenient solution for all your inflation needs.

# Product Introduction

# Bitsman




--The top tire mobility kit provider



## Inflator

Project	Specification value
Product name	Inflator
Model number	AC1
Inflator dimensions	150*150*58
Inflator weight	0.72kg
Operating voltage	DC9V-16V
Operating current	≤15A
Pressure automatically released at	5±0.5bar
Pressure gauge accuracy	±0.1bar
Nanometer Measurement	0-6bar
Inflator 45L air tank (0-3.0bar)	≤8min
Length of wire	3060mm±50mm
Sealant hose Length	≥500mm
Air hose length	≥550mm
Core Valve Type	VG8 universal thread
Sound range	≤90decibel
Sustainable working hours	≥30mins
Inflator durability test	≥100 cycles
Operating temperature range	-30℃ ~ 70℃



Optional Product List		
Product Name	Product picture	Product Use Method
Battery Clamp	 A black battery clamp with a cigarette lighter female socket interface on one end and a red positive pole and a black negative pole on the other end.	One end is a cigarette lighter female socket interface, and the other end is a positive and negative level red and black chuck, a red positive pole and a black negative pole correspond to the positive and negative poles of the vehicle-mounted battery, and the positive and negative levels of the vehicle-mounted battery are marked with a plus sign and a minus sign.
Extension Hose	 A yellow, coiled extension hose.	Suitable for vehicles with large and long body size, such as the power cord and inflation hose length of the inflator can not reach part of the tire air nozzle after plugging in the cigarette lighter, the use of this extension hose can solve the problem, the longest extension length of the hose is 3 meters
Gas Needle	 A small, black and silver gas needle.	English French air valve adapter, basketball football pin connector
The Nail Puller	 A red-handled nail puller with a black handle and a silver nail head.	The nail puller consists of a nail head, a nail pulling plate, a nail groove and a handle. When in use, align the nail head with the nail, press the handle to make the nail head enter the nail hole, and then lift the handle to pull out the nail.

04

Contact us

---




# Contact us

<https://www.facebook.com/settings?tab=profile&section=username>



Facebook



Instagram

<https://www.youtube.com/@BITSMANAUTO>

<http://www.twitter.com/bitsmanauto>



Twitter



YouTube

<https://www.youtube.com/@BITSMANAUTO>

Contact us

**Bitsman**  
--The top tire mobility kit provider



Please scan the QR code to watch the product operation video.



Please scan the QR code to follow our Wechat Official Account.



Contact us

Bitsman

--The top tire mobility kit provider

# Drop us a line!



Tel/Fax:0512-66152800

Cell/Whatsapp: +008615900974134



Wechat/Skype:flyingjennie

Email:sales@bitsmanauto.com



Website:www.bitsmanauto.com

Thank you for watching.