


# Egoldvan Industry Co., Limited

## Specification Sheet



<b>The name of project:</b>		SLT300	<b>Draft Date:</b>	2023.04.13	
<b>The name of product:</b>		Tire sealant	<b>Last revision date:</b>		
<b>Part number:</b>		SLT300	<b>version:</b>	P01	
<b>Design basis:</b>		Technical specifications			
Number	Project	Specification value	Products' introduction&photos		
1	Overall Dimensions	Φ89×138.5	<p>1.The tire sealant is researched,produced and made by our company independently.The main raw material of the tire sealant are natural latex , propylene glycol and so on, which don't corrode type and rim. 2.The tire sealant can fix the worn tire quickly with the use of inflator.(we can fix the damaged nails which is ≤φ6mm)</p>		
2	Gross weight ( kg )	0.5kg			
3	Tire sealant Volume	300mL			
4	Tire sealant Validity	On-board condition 5 years			
5	Tire sealant performance	Applicable Temp. Range			-30℃~70℃
6		Puncture Diameter			Fix the damaged punctures which is ≤φ6mm
7	Tire sealant melting point	115℃ no boiling			
8	Tire sealant freezing point	-70℃ no solidification			
9	PH value	7~9			
10	Smell	Slight mild rubber oder			
11	Colour	Milky white			
12					
13					
14					
15					
16					
17					
18					
19					
20					
21					
22					
23					